

Tercet® 5' Whirlpool Bath K-1160-HD



Features

- Single-speed whirlpool offers performance and value, with 6 fully adjustable jets.
- Hydromassage flow and direction can be controlled at each jet.
- Built-in heater.
- Corner layout minimizes footprint without compromising bathing area.
- Spacious design accommodates up to two bathers.
- Molded lumbar supports and armrests offer extra comfort while bathing.
- Multiple pump location options give you more choices for installation and access. (See specification sheet for pump locations.)
- Center drain.

Material

Acrylic

Hydrotherapy

Whirlpool

Installation

Drop-in

Recommended Products/Accessories

K-11677 Bath Drain K-1491 Bath/Whirlpool Pillow K-1601 Bath/Whirlpool Footstop K-7259 Clearflo Bath Drain K-37382 45" Rough-in Cable Bath Drain



Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 Greenguard UL 2818 - Gold

KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty KOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes


Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond





Tercet® 5' Whirlpool Bath K-1160-HD



Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Pump: 120 V, 15 A, 60 Hz Heater: 120 V, 15 A, 60 Hz

Technical Information

All product dimensions are nominal.

Installation: Drop-in Center Drain location:

52" x 38-3/4" (1321 mm x 984 mm) Basin area, bottom: Basin area, top: 61" x 46-1/4" (1549 mm x 1175 mm)

Weight: 131 lbs (59.4 kg) Minimum floor load: 39 lbs/ft2 (190.4 kg/m2)

15" (381 mm) Water depth: Water capacity: 96 gal (363.4 L)

Electrical component Pump: 120 V, 7.5 A, 60 Hz

rating: Heater: 120 V, 12.5 A, 60 Hz, 1500 W

Pump speed: Single

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Provide one grounded electrical outlet within 24" (610 mm) of each component.

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.

